

ROOF KIT LX COMFORT ABSORBER ROPE GRAB 20M 2QT

P709GCL

Kit consisting of a 2-point fall arrest harness with automatic buckles, a rope grab with absorber and 2 automatic quarter turn carabiners, and an anchorage sling

Benefits

- Ready-to-use kit
- Stretch shoulder straps
- Automatic quarter turn carabiners

Uses

- Construction
- Industry
- Logistics
- Services

Packaging

- Unit of sale: kit
- Supplied in a hard-bottom storage bag
- Box of 5 units

Description	Code
Roof kit	68 432 960

Also sold separately	
LX Comfort harness	68 432 979
LX16 carabiner	68 433 029

Standards

- EN 361: 2002
- EN 362: 2004B
- EN 795: 2012 Type B
- EN 353-2: 2002



Description

HARNESS

- Harness with 2 attachment points (sternal - dorsal)
- Aluminium dorsal D-ring = durable
- Aluminium automatic buckles = quick to put on / no need to readjust the straps every time you use them
- Stretch straps at the shoulders = freedom of movement
- Wearer identification label
- Tested at 140kg
- Colour: red/black

Composition:

- Straps: polyester
- Automatic buckles: aluminium
- Dorsal D-ring: aluminium

KERNMANTLE ROPE GRAB

- Stainless steel rope grab, resistance > 15kN
- 20m polyester kernmantle rope, diameter 12mm
- Thimbled buckles = added durability
- Transparent sheath = visual inspection of the seams
- Energy absorber with strap
- Tested at 140kg

2 CONNECTORS

- Zinc-plated steel LX16 carabiners
- Automatic quarter turn
- Resistance 25kN
- 16mm opening

ANCHORAGE SLING

- Polyester straps
- Length 0.8m / Width 20mm
- Static strength (as per EN 566) > 22kN
- Breaking strength: 30kN

