

HANDLITE OGT NIT

P70R89K

Lightweight handling glove suitable for oily and damp environments









Benefits

- Made from 97% recycled polyester yarn
- Fine knitting (15 gauge) gives the glove great flexibility for superior comfort
- Compatible for use with touchscreens

Description

- · Suitable for oily and damp environments
- · Recycled polyester knitted glove, green, seamless, 15 gauge
- Black double coating made of nitrile foam and TPU on palm and front of the fingers
- · Excellent abrasion resistance for longer glove life

Category II gloves designed to provide protection against mechanical risks only

Uses

- Lightweight handling in dry or oily environments
- Handling greasy or oily items
- Automotive, transport, metallurgy
- Construction work

Composition

• Material: 97% recycled polyester, 3% spandex

Coating: foam nitrileLength: 22 to 26cm

Packaging

- · Unit of sale: pair
- Set of 10 pairs
- Box of 100 pairs

| Size | Code |
|--------|------------|
| T7 - S | 68 905 710 |
| T8 - M | 68 905 729 |
| T9 - L | 68 905 737 |

| Size | Code |
|-----------|------------|
| T10 - XL | 68905745 |
| T11 - XXL | 68 905 753 |

Standards



| Abrasion resistance | 4/4 |
|----------------------------|-----|
| Cut-resistance (coup test) | X/5 |
| Tear resistance | 2/4 |
| Puncture resistance | 1/4 |
| TDM cut | X/F |
| Dexterity | 5/5 |
| | |

[&]quot;X" means that the test has not been performed.

EN ISO 21420



