

## HANDSAFE XP 961

P702LQQ

Long-sleeved cut-resistant protective glove  
TDM F

### Benefits

- Extrem cut resistance: TDM F
- Level 4 for abrasion and tear resistance
- Touch screen glove
- Second-skin effect for incomparable sensitivity and precision

### Applications

- Automobile industry
- Glass and metal industries
- Handling of sharp-edged parts
- Metal-working industry
- Assembly workstations

### Packaging

- Unit of sale: pair
- Set of 5 pairs
- Box of 50 pairs

| Sizes   | SKU numbers |
|---------|-------------|
| T6 - XS | 66 338 843  |
| T7 - S  | 66 338 851  |
| T8 - M  | 66 338 878  |

| Sizes     | SKU numbers |
|-----------|-------------|
| T9 - L    | 66 338 886  |
| T10 - XL  | 66 338 894  |
| T11 - XXL | 66 338 908  |



DURABILITY



TOUCH SCREENS

### Description

- Ergonomic, seamless, 18 CUT XP gauge knitting for a unique comfort experience
- Extrem cut resistance
- Made from high performance polyethylene fibers (HPPE), metallic fibers, nylon and spandex
- Black nitrile reinforcement between thumb and forefinger for greater durability
- Grey polyurethane coating on the palm and face of the fingers

*Category II gloves designed to provide protection against mechanical risks only*

### Composition

- Material: high performance polyethylene fibers, metallic fibers, nylon and spandex, 18 gauge
- Coating: grey polyurethane
- Length: 22 to 27 cm depending on the size

### Standards - Performance levels

EN 388



4X43F

|                            |     |
|----------------------------|-----|
| Abrasion resistance        | 4/4 |
| Cut resistance (coup test) | X/5 |
| Tear resistance            | 4/4 |
| Puncture resistance        | 3/4 |
| Cut resistance (TDM test)  | F   |

"X" means that the test has not been performed

EN420



Cat II

