

HANDSAFE XP 971 N P708KFA

Cut protection glove TDM F

Benefits

- Extreme cut protection: TDM F
- CUT XP 15 Gauge: fine knitting for more comfort
- Glove without glass fiber or stainless steel
- Contact heat resistant
- Touch Screen glove

Uses

- Handling of heavy greasy or oily sharp objects
- Assembly workstations
- Waste collection
- Automobile industry
- Glass and metal industries
- Metal-working industry

Packaging

- Unit of sale: pair
- Set of 5 pairs
- Box of 50 pairs

Size	Code	Size	Code
T6 - XS	68 041 775	T9 - L	68 041 805
T7 - S	68 041 783	T10 - XL	68 041 813
T8 - M	68 041 791	T11 - XXL	68 041 821



CUTXP



DURABILITY



TOUCHSCREEN



THERMAL PROTECTION

Description

- Designed with high performance fibers without glass fibers or stainless steel
- Foam nitrile coating, "second skin" effect, on palm and fingers
- CUTXP 15 gauge knitting for a unique comfort experience
- Good grip in oily conditions
- Resistant to contact heat
- Maximal cut protection
- Nitrile reinforcement between thumb and index finger for improved durability

Category II gloves designed to provide protection against mechanical risks only

Composition

- Material: high performance polyethylene fibers (HPPE), tungsten, polyester and spandex
- Coating: Black nitrile foam
- Length: 22 to 27 cm depending on size



STANDARD
100
CQ 1331/1
IFTH

Standards

EN 388



4X42F

Abrasion resistance	4/4
Cut resistance (coup test)	X/5
Tear resistance	4/4
Puncture resistance	2/4
Cut resistance (TDM test)	F



NO GLASS/STEEL

EN 407



X1XXXX

Resistance to flammability	X/4
Contact heat	1/4
Convective heat	X/4
Radiant heat	X/4
Small splashes of molten metal	X/4
Large splashes of molten metal	X/4

"X" means that the test has not been performed.

EN ISO 21420