

AIR'POCKET FFP3 NR D

P702J7V

Foldable filtering half-mask with valve

Benefits

- Protection against highly toxic particles and against solid and/or liquid aerosols: dusts from: chromium, cobalt, lead, cadmium, hardwoods (oak, beech), silica and granite, and from asbestos (low concentration), ceramic fibres and legionella (short duration)
- Filters out 99 % of dust (mean diameter: 0.6 microns)

Tests

- 120 mg loading test (as per the requirements of amendment A1: 2006 of standard 143: 2000)
- Tested using dolomite dust (resistance to clogging and longer service life in high dust environments)
- This test is an optional requirement of standard EN 149

Packaging

- Box of 10 masks
- Carton of 20 boxes

| Size | Code |
|-------------|------------|
| Unique size | 58 224 359 |



Description

- Foldable, non reusable, filtering half mask for protection against particles
- Extremely fine and light filtering media for wear comfort even over long periods
- Nose clip to improve sealing to the face
- Elastic band (no staples) for easy adjustment
- The mask can be kept off the face on standby using a strap
- Sealed tabs (no staples and no additional plastic parts)
- Flat-fold - 2-panel design (no contamination on the inside)
- Lightweight and comfortable
- Individual packaging (for optimal hygiene)
- One size fits all
- Made in Europe

Only available as a valved version for greater respiratory comfort and no fogging for persons wearing glasses

Valve colour coding for quick identification of the protection level

Composition

Filtering media: Polypropylene

Nose clip: Polypropylene-coated steel

Elastic strap: Synthetic latex

Nasal foam: Grey polyurethane

Valve body: Polypropylene

Valve membrane: Vulcanised rubber

WEL*: 50 times the WEL

Maximum duration of use: 8 hours during a single period of work

NR marking: Not Reusable

Shelf-life: 5 years starting from the date of manufacture (under satisfactory storage conditions):

> Maximum relative humidity: <80%

> Storage temperature between -20°C and +40° C

Do not use: If oxygen level is < 17 % or in the assumed or potential presence of toxic gases

*WEL: Workplace exposure limit

The average concentration, during an 8-hour working day and a 40-hour working week, at which the daily exposure does not endanger the individual's health

Standards

EN 149 : 2001 + A1 : 2009