

STEP'WIND OGT

P70XMS7

S1PL HRO SR ESD
low-cut safety trainer

Benefits

- Highly breathable, ultra-lightweight low-cut trainer: 460 g in size 42
- 26% recycled upper*

Uses

- Industry
- Logistics
- Maintenance
- Services
- Finishing work
- Dry environments

Packaging

- Unit of sale: pair
- From 36 to 39 and 46 to 48: boxes of 5 pairs
- From 40 to 45: boxes of 10 pairs

| Size | Code | Size | Code |
|------|------------|------|------------|
| 36 | 71 505 669 | 43 | 71 505 731 |
| 37 | 71 505 677 | 44 | 71 505 758 |
| 38 | 71 505 685 | 45 | 71 505 766 |
| 39 | 71 505 693 | 46 | 71 505 774 |
| 40 | 71 505 707 | 47 | 71 505 782 |
| 41 | 71 505 715 | 48 | 71 505 790 |
| 42 | 71 505 723 | | |



Description

- Non-magnetic low-cut safety shoe
- 50% recycled polyester upper with breathable Flyknit side ventilation panels
- Front and heel PU reinforcement for greater abrasion and impact resistance
- Breathable 3D mesh lining made from 50% recycled polyester
- Impact-resistant fibreglass toe cap (up to 200 J)
- Removable sockliner with 50% recycled mesh
- 50% recycled anti-perforation non-metal sole, compliant with the EN ISO 20345 standard
- Heat and abrasion resistant EVA/rubber sole - SR adhesion coefficient compliant with the EN ISO 20345 standard
- Complies with ESD requirements under the BS EN IEC 61340-4-3:2018 standard
- Colours: blue/grey
- Weight (size 42): 460 g

*excluding toe cap

Standards

- EN ISO 20345: 2022 + A1: 2024 S1PL HRO SR
- BS EN IEC 61340-4-3: 2018 ESD